



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station

Product Name	Duracell Portable Power Station (Lithium-Ion Batteries)
Chemical System	Lithium Nickel Cobalt Manganese Oxide
Description	Duracell Branded Consumer Lithium Battery
Product Category	Electro-Technical Device
Use	Portable power source for electronic devices.
Global sub-brands (Retail)	Duracell
Model Numbers	RT300, D500, RT600, RT1000
Principles of Operation	A battery powers a device by converting stored chemical energy into electrical energy.
Document ID	PSDS – Lithium Ion PPS
Information Contact	SDS@duracell.com
Date Updated	6/13/2022
Preparer	Product Safety & Regulatory

This Product Safety Data Sheet (PSDS) provides relevant battery information to retailers, consumers, OEMs, and other users requesting a GHS-compliant PSDS. Articles, such as batteries, are exempt from GHS PSDS classification criteria. The GHS criteria is not designed or intended to be used to classify the physical, health, and environmental hazards of an article. Branded consumer batteries are defined as electro-technical devices. The design, safety, manufacture, and qualification of branded consumer batteries follow ANSI and IEC battery standards. This document is based on principles set forth in the following hazard communication approaches ANSI Z-400.1, GHS, JAMP AIS, and IEC 62474.

Section 1: MANUFACTURER’S INFORMATION

Importer’s Name and Address	Duracell US Operations, Inc. 14 Research Drive, Bethel, CT USA 06801
US Telephone	(203) 796-4000
Global Website	www.duracell.com
Consumer Relations	North America 1-800-551-2355 (9:00 AM - 5:00 PM EST)

Section 2: HAZARD IDENTIFICATION

Product is a sealed article, not a mixture or substance. Exposure to contents inside the sealed battery will not occur unless the battery leaks, is exposed to high temperatures, or is mechanically abused.

Section 3: COMPOSITION

Applicable Battery Industry Standards	UN 38.3, ETL, CEC, FCC, DOE
Description	Branded Consumer Battery

COMPONENTS	INGREDIENTS	CAS NUMBER	
------------	-------------	------------	--



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station

Lithium Nickel Cobalt Manganese Oxide	12190-79-3	25-35%
Graphite	77842-42-5	15-20%
Polyvinylidene	24937-79-9	1-5%
Acetylene Black	1333-86-4	0.5-3%
Electrolyte: (Ethyl Methyl Carbonate (EMC)/ Dimethyl Carbonate (DC)/ Ethylene Carbonate (EC))	623-53-0 616-38-6 96-49-1	5-15%
Aluminum	7429-90-5	21-23%
Copper	7440-50-8	10-11%
Lithium Hexafluorophosphate	21324-40-3	10-15%

Section 4: FIRST AID MEASURES

(In case of electrolyte leakage from the battery.)

Eye Contact	Flush thoroughly with copious amounts of running water for at least 30 minutes. Hold eyelids open to assure thorough flushing. Seek immediate medical attention.
Skin Contact	Immediately remove contaminated clothing and shoes while flushing with water. Continue to flush exposed skin with water for at least 15 minutes. Seek medical attention if irritation develops and persists. Launder contaminated clothing before reuse and discard shoes and other items that cannot be decontaminated.
Ingestion	Swallowing is not anticipated due to battery size. Irritation to the internal/external mouth area may occur following exposure to a leaking battery. Do not induce vomiting, give food or drink. Seek medical attention immediately.
Note to Physician	For information on battery identification and treatment, call the 24-hour National Battery Ingestion Hotline (800-408-8666) . Additional treatment information is available from the National Capital Poison Control Center Button Battery Ingestion Triage and Treatment Guideline : https://www.poison.org/battery/guideline . http://globalcrisis.info/poisonemergency.html#AAA
Poison Center World Directory	http://globalcrisis.info/poisonemergency.html#AAA
Inhalation	Contents of leaking battery may be irritating to respiratory passages. Move to fresh air. Seek medical attention if irritation persists.

Section 5: FIRE FIGHTING MEASURES

	In case of fire, you can use fire extinguishers appropriate for a solid material fire; the recommended sequence is water or water mist, sand, CO ₂ , powder. Use any extinguishing media appropriate for the surrounding materials. For incipient (beginning) fires copious amounts of water are effective in cooling burning lithium ion batteries. Fire fighters should use appropriate PPE for the fumes and heat
--	---



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station

Extinguishing Media	In case of fire, you can use fire extinguishers appropriate for a solid material fire; the recommended sequence is water or water mist, sand, CO2, powder. Use any extinguishing media appropriate for the surrounding materials. For incipient (beginning) fires copious amounts of water are effective in cooling burning lithium ion batteries. Fire fighters should use appropriate PPE for the fumes and heat
Unusual Fire and Explosion Hazards	Not classified as an oxidizer based on test data, however, thermal decomposition of product may release oxygen that can accelerate rate of combustion of surrounding fire.
Advice for Fire-Fighters	Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Fight fire from a distance or protected area. Cool fire-exposed containers to prevent rupture. Do not breathe smoke, gases or vapors generated. Detailed information on fighting a lithium metal battery fire can be found in US DOT Emergency Response Guide 138 (Substances–Water–Reactive). Keep unprotected persons away.

Section 6: ACCIDENTAL RELEASE INFORMATION

	Clean-up personnel should wear appropriate protective clothing to prevent eye and skin contact and inhalation of dust. Ventilate area of spill. Avoid creating airborne dust. Eliminate all sources of ignition. Keep spilled material away from combustible materials.
Personal Precautions, Protective Equipment and Emergency Procedures	Clean-up personnel should wear appropriate protective clothing to prevent eye and skin contact and inhalation of dust. Ventilate area of spill. Avoid creating airborne dust. Eliminate all sources of ignition. Keep spilled material away from combustible materials.
Environmental Precautions	Avoid release to the environment without proper government permits. Prevent entry into storm sewers and waterways. Report spills as required by local and national regulations.
Methods and Material for Containment and Cleaning Up	Do not use combustible absorbents or dust control products. Carefully collect material with a scoop. Do not generate airborne dust. Place in appropriate container for disposal. Rinse the spill area with water after clean-up is complete. Collect rinse water for appropriate treatment and disposal. Remove any spilled liquid with absorbent material and contain it for disposal.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling	Do not short circuit, or dispose into fire. Do not crush for Safe Handling
Conditions for Safe Storage (Including any Incompatibilities)	<p>Store in cool, dry place in original packaging. Do not store with acids. Store away from reducing agents.</p> <p>Operating Temperature 0°C to 40°C</p> <p>Storage Temperature (for shipping state) Short Term (less than three months) -10°C to 45°C Long Term Storage 6°C to 29°C</p>



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

No PPE is necessary

Consumer Product

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Article

Physical Description Not Applicable

Chemical Properties Not Applicable

Section 10: STABILITY AND REACTIVITY

Stable and Non-Reactive under 60°C.

Section 10: STABILITY AND REACTIVITY

The chemicals in this product are contained in a sealed unit and exposure does not occur during normal handling and use.

Venting cells may have ether smell. If strong smell persists, or cell leakage is observed, it should be disposed of per local regulations.

Mercury, Lead, and Cadmium are not used in the cell. (**Note:** If traces are found, they may be from impurity of raw materials, not added as part of the recipe.)

Section 12: ECOLOGICAL INFORMATION

The chemicals in this product are contained in a sealed can and exposure does not occur during normal handling and use.

Venting cells may have ether smell. If strong smell persists, or cell leakage is observed, it should be disposed of per local regulations.

Mercury, Lead and Cadmium are not used in the cell. (**Note:** If traces are found, they may be from impurity of raw materials, not added as part of recipe.)

Section 13: DISPOSAL CONSIDERATIONS

Collect and Proper Disposal per local regulations. Recycling is suggested.

Section 14: TRANSPORTATION INFORMATION

UN38.3 TEST Summary Documents



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station

	UN38.3 Test Summary Documents that are required by the UN Model Regulations, can be requested by sending an email request to UN38.3_duracell@duracell.com .	
	Duracell lithium metal batteries are produced and delivered in accordance with current IATA/ICAO regulations. Duracell lithium metal batteries can be by air shipped in accordance with ICAO or IATA. Shipping packages for all DURACELL lithium cells/batteries are designed to prevent short circuits, movement within the package, damage to the cells/batteries, and release of the package contents. Persons who prepare or offer lithium batteries for transport are required by regulation to be trained to the extent of their responsibility. The information in this section is provided for informational purposes only. The transportation of lithium-ion batteries is regulated by ICAO, IATA, IMO, ADR, and US DOT.	
UN Identification Number/Shipping Name	UN3480, Lithium-ion Battery, 9	Wattage – Wh rating
	Model	292
	RT300	515
	D500	569
	RT600	1050
	RT1000	
IATA 63rd, 2022 edition	PI965 Section IA All models are greater than 100 Whr State of Charge (SoC) must be below 30%	
IMDG	Fully regulated battery only shipment (UN3480, Lithium-ion Battery, 9)	
US DOT	RT300; classified as a medium battery – UN packaging exemption for gross shipments 30 kg or less. All other models are classified as a larger battery – Fully regulated shipment	
Emergency Transportation Hotline	CHEMTREC 24-Hour Emergency Response Hotline	
Emergency Transportation Hotline	Within the United States, call: 1-800-424-9300	
	Outside of the United States, call: 1-703-527-3887 (Collect)	

Section 15: REGULATORY INFORMATION

GHS Article Exception	Section 1.3.2.1
------------------------------	-----------------

Section 16: OTHER INFORMATION

A Lithium-ion battery is a safe consumable product under recommended or normal usage conditions. It is not a dangerous substance or mixture. There are no PSDS supply requirements for Lithium-ion batteries by the Globally Harmonized System (GHS). Duracell is providing this PSDS as a service to its customers and other users who may make use of alkaline batteries in the workplace.

Disclaimer: This PSDS is intended to provide a summary of our knowledge and guidance regarding the use of this product. The information contained here has been compiled from sources considered by Duracell US Operations, Inc. to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations. This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. Duracell US Operations, Inc. assumed no responsibility for injury to the recipient or third parties, or any damage to any property resulting from the misuse of the product.

***** End of PSDS *****



PSDS – Product Safety Data Sheet

Lithium-Ion Battery – Portable Power Station